

LAWNMOWER RULES AND REGS

1. Lawnmower "MUSTS"
 - a. Must use all lawnmower parts unless otherwise indicated
 - b. Working tether switch/kill engine cord
 - c. Width limit 38" to the most outermost point of mower
 - d. Unlimited length allowed
 - e. Must look like a lawnmower
 - f. No sharp edges (no protrusions)
 - g. Must have a lawnmower hood, no fabricated hoods
 - h. Fenders optional, but not mandatory – no fabricated fenders
 - i. Need nerf bars or mower deck. Needs to be center of axle height and 3' max. from the front and rear tires and no wider than the outside of the tires. Floorboard to nerf bar, no more than 3" gap
 - j. Must have lawnmower seat that is 15" min from the ground to where you sit with a back that is a min. of 3" high. May offset seat 2" max.
 - k. NO FRONT BUMPERS
 - l. Must have a rear bumper that is axle height and to be 4" to 8" in height. Needs to be as wide as rear tires
 - m. Must have a round (360 degree) steering wheel
 - n. No handle bars
 - o. No mower blades
 - p. Front steering mower only
 - q. No articulate tractors (pivot in middle)
 - r. Foot/hand throttle allowed
2. Brakes
 - a. On live axle mowers, brakes need to be mounted on the live axle
 - b. Brakes must work at all times
 - c. Brakes of any style or type allowed
 - d. Hand-Brake on steering wheel recommended but not mandatory
 - e. If using foot brake, it is recommended that it is on the left side. Clutch and brake must be on opposite sides
3. Clutch
 - a. Foot operated mechanical clutch only
 - b. Clutch must work at all times
 - c. No electric clutches
 - d. No centrifugal clutches
4. Numbers
 - a. Numbers to be displayed on front, rear and both sides of mower with a min. size of 6"
 - b. All drivers MUST REGISTER their number prior to the start of the season
 - c. One or two digit numbers only – NO LETTERS
 - d. There will be a one time charge \$10.00 for number registration, due and payable at tech inspection or before the first race of the season
5. Engine
 - a. Max. engine size is 25HP
 - b. No off setting engines. Motor shaft must be center of frame rails
 - c. Vertical lawnmower engines only – No horizontal shaft engines
 - d. Race fuel allowed
 - e. No alcohol burning engines or mixed with fuel
 - f. No nitrous oxide
 - g. No variable speed pulleys
 - h. MANDATORY – if engine is exposed, MUST have cover over flywheel
 - i. No two stroke engines
6. Steering / Tires
 - a. Mandatory, to plate inside or weld center hub or rims
 - b. All classes, except stock, may run go cart spindles, hubs and rims
 - c. Steering parts between spindles and steering wheel may be after market or lawnmower parts
 - d. Lawnmower tires only

- e. No ATV tires or rims
 - f. NO go cart tires
 - g. Live axles with pillow block or carrier bearings allowed
 - h. Steering wheel may be offset 2" max.
7. Chassis Fabrication
- a. Only steel box tubes 1" x 2" min. and u channel steel 1" x 2"
 - b. Must be straight from front axle to rear bumper
 - c. Engine plate steel only and front plate steel, or stamped frames are legal
 - d. No round tube chassis or aluminum or chomemoly
 - e. No off setting chassis
 - f. No adjustable camber
 - g. Solid suspension only – no springs
 - h. Frame height 4" min from lowest point of frame
 - i. Frame rails same height on both sides from the ground
8. Tech Inspection
- a. Non legal mowers will NOT run on race day unless fixed and approved by Tech Inspectors
9. No off setting anything unless otherwise above.

~ Rules and Regs are from nepalawnmowerracing.com~